

INSTRUCTIONS

GRANITEPOX™ GRANITE IMITATION EPOXY PAINT

VOLUME

1 kg

ABOUT THE ITEM

Granite imitation epoxy floor paint.

Ingredients: phenolic epoxy resin 40%, color paddle 14%, active diluent 5%, barite 40%.



HOW TO USE

- **Mixing:** Stir thoroughly after opening. Mix component A (main agent) and component B (curing agent) in the specified ratio 7 : 1.
- **Application methods:** rolling, scraping, spraying, brushing, and troweling.
- **Conditions:** moisture content below 8%, humidity below 55%; avoid application if relative humidity is above 80% or temperature is below 10°C.
- **Drying time:** ca. 12 hours.
- **COVERAGE:** 0,6–0,7 m².
- **Storage:** store in a cool, ventilated area, protected from moisture and sunlight.

WARNINGS

- Safety instructions: This is a chemical product. Avoid ingestion, seek immediate medical help if swallowed. Follow safety regulations for residue disposal. Avoid inhalation. Can cause respiratory irritation. Avoid eye contact. In case of eye contact, rinse with warm water. Avoid exposing to extreme temperatures. Avoid exposing to flammable liquids and materials.
- **DANGER!**



- Important notice: Product quality is ensured, manufactured per national standards. While the information provided is accurate, the company does not assume responsibility for outcomes under varying application conditions.

- Keep out of the reach of children.
- Dispose of contents/container in accordance with national regulations.
- Shelf life: 24 months.
- Made in China.

