# **INSTRUCTIONS**

# FLEXIBLE POLYUREA GROUTING SEALANT GROUTPRO™

## **VOLUME**

1 kg

#### **ABOUT THE ITEM**

The product is a self-leveling caulking glue. Single component, natural curing, strong bonding, long-lasting, elasticity, aging resistance.

Main uses: Adhesion and sealing of expansion, settlement, cutting etc. of roads, airport runways, squares, wall pipes, docks, roofs, underground garages, and basements. Anti-leakage sealing of refineries and chemical plants. Adhesion and sealing of industrial floors such as epoxy floors and various paint surfaces. Waterproof sealing of roof, cracks, expansion joints, structural walls, joints between materials, metal plate boxes, etc.



#### **HOW TO USE**

- Clean the surface before you apply the product.
   The surface must be dry and clean, free of dust and oil.
- Install the caulking glue nozzle, penetrate the bottom of the construction gap and inject the caulking glue into the construction seal.
   Recommended depth is 1-2 cm. Fill deeper gaps with foam strips or fine sand before applying the caulking glue.
- As the joint will expand and contract with temperature changes, the surface of the caulking glue should be about 2 mm lower than the road surface after you finish.
- Recommended construction temperature: 5-35°C.
- Use temperature: -40°C-80°C.
- Reference dosage: Taking a gap of 1 cm depth and 1 cm width as an example, 500 ml of caulking glue can be used for about 6 m.

## **WARNINGS**

- Use it as soon as possible after opening the bag to avoid product curing affecting use.
- Weather temperature affects the curing time. It is normal for curing time to be longer in winter.
- The product takes about 24 hours to fully cure at room temperature, and 2 hours to dry on the surface.
- Danger!





- Do not eat the product.
- For external use only.
- Keep out of the reach of children.
- Avoid contact with eyes.
- Discontinue use if signs of irritation or rash occur.
- Causes skin irritation.
- Causes serious eve irritation.
- May cause an allergic skin reaction.
- Suspected of causing cancer.
- Causes damage to organs through prolonged or repeated exposures.
- Do not eat, drink or smoke when using this product. Wear eye/face protection.
- If in contact with skin, wash it off and seek medical attention immediately if necessary.
- If on clothes, wash it out immediately and pay attention to clothing protection during use.
- Seal and store in a cool and dry place.
- Store at a temperature of 5°C-25°C and a humidity of ≤50%RH.
- Ingredients: Co-Formula CFS-114, 1,2-Benzene-3,4,5,6-d4-dicarboxylicacid, di octyl ester (9CI), Oxirane, methyl-, polymer with gxirane acetate, dioxosilane, oxomagnesium, hydrate, 3-Aminopropyltrimethoxysliane.
- Dispose of contents/container in accordance with national regulations.
- Shelf life: 12 months.
- Made in China.



